



T11UM

Engine MITSUBISHI , S3L2-SD
Alternator MECC ALTE , ECO3-3LN

STANDARD FEATURES

- Mechanical governor
- Mechanically welded chassis with antivibration suspension
- Power circuit breaker
- Radiator for wiring T° of 50°C [122°F] max with mechanical fan
- Protective grille for fan and rotating parts
- 9dB(A) silencer supplied separately
- Charged DC starting battery with electrolyte
- 12 V charging alternator and starter
- Supplied with oil and coolant -30°C
- User manual and commissioning guide



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
240MONO	10.0 / 10.0	9.1 / 9.1	41.7	Length: 1405mm [55in] Width: 715mm [28in] Height: 1053mm [41in]	417kg [919 lbs] Net 468kg [1032 lbs] Gross



POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. A 10% overload capability is available for a period of 1 hour within 12-hour period of operation, in accordance with ISO 3046-1 –

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions 25 °C Air Intlet Temp, 100 m A.S.L. 60 % relative humidity. All engine performance data based on the above mentioned maximum continuous ratings.

Type	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
 M126	72.5	62.5	Length: 1750mm [69in] Width: 715mm [28in] Height: 1230mm [48in]	565kg [1246lbs] Net 616kg [1358lbs] Gross	50 L
 M126-DW	72.5	62.5	Length: 1797mm [71in] Width: 775mm [31in] Height: 1391mm [55in]	646kg [1424lbs] Net 730kg [1609lbs] Gross	93 L





ENGINE SPECIFICATIONS

STANDARD FEATURES	Manufacturer / Model	MITSUBISHI S3L2-SD , 4-strokes, Athmo , [N/A] 3 X
	Cylinder Arrangement	L
	Displacement	1.31L [79.9C.I.]
	Bore and Stroke	78mm [3.1in.] X 92mm [3.6in.]
	Compression ratio	22 : 1
	Rated RPM	1800 Rpm
	Piston Speed	5.52m/s [18.1ft./s]
	Max. stand by Power at rated RPM	13.86kW [19BHP]
	Frequency regulation, steady state	+/- 2.5%
	BMEP	6.36bar [92psi]
	Governor : type	MECA
EXHAUST SYSTEM	Exhaust temperature	400°C [752°F]
	Exhaust gas flow	43.9L/s [93cfm]
	Max back pressure	700mm CE [28in. WG]
FUEL SYSTEM	110% (Stand By power)	[N/A]
	100% (of the Prime Power)	4L/h [1.1gal/hr]
	75% (of the Prime Power)	3.2L/h [0.8gal/hr]
	50% (of the Prime Power)	2.5L/h [0.7gal/hr]
	Max. fuel pump flow	18L/h [4.8gal/hr]
OIL SYSTEM	Total oil capacity w/filters	4.2L [1.1gal]
	Oil Pressure low idle	0.5bar [7.2psi]
	Oil Pressure rated RPM	4bar [58.0psi]
	Oil consumption 100% load	0.022L/h [0.006gal/hr]
	Oil capacity carter	3.7L [1.0gal]
THERMAL BALANCE	Heat rejection to exhaust	12kW [682Btu/mn]
	Radiated heat to ambient	1.5kW [85Btu/mn]
	Heat rejection to coolant	12.2kW [694Btu/mn]
AIR INTAKE	Max. intake restriction	200mm CE [8in. WG]
	Engine air flow	16.4L/s [35cfm]
COOLANT SYSTEM	Radiator & engine capacity	4.2L [1.1gal]
	Max water temperature	111°C [232°F]
	Outlet water temperature	93°C [199°F]
	Fan power	0.4 kW
	Fan air flow w/o restriction	0.7m3/s [1483cfm]
	Available restriction on air flow	10mm CE [0.4in. WG]
	Type of coolant	Gencool
	Thermostat	82-95 °C
EMISSIONS LEVEL	PM	N/A
	CO	N/A
	Nox	N/A
	HC	N/A

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com





ALTERNATOR SPECIFICATIONS

GENERAL DATAS	Manufacturer	MECC ALTE
	Type	ECO3-3LN
	Number of phase	1
	Power factor (Cos Phi)	1
	Altitude	1000
	Overspeed	[N/A]
	Pole : number	4
	Exciter type	NO
	Insulation : class, temperature rise	H / H
	Voltage regulator	SR7/2
	Total harmonics (TGH/THC)	[N/A]
	Wave form : NEMA = TIF – TGH/THC	[N/A]
	Wave form : CEI = FHT – TGH/THC	2
	Bearing : number	1
	Coupling	Direct
	Voltage regulation 0 to 100% load	[N/A]
	Recovery time (20% Volt dip) ms	[N/A]
SKVA with 90% of nominal sustained voltage (at 0.4PF)	N/A	
OTHER DATAS	Continuous nominal rating @ 40°C	15 kVA
	Standby rating @ 27°C	15 kVA
	Efficiencies @ 4/4 load	86.7 %
	Air flow	0.058m ³ /s [122.89cfm]
	Short circuit ratio;50 (Kcc)	1.1
	Direct axis synchro reactance unsaturated (Xd)	140 %
	Quadra axis synchro reactance unsaturated (Xq)	78 %
	Open circuit time constant;50 (T'do)	0.84 ms
	Direct axis transient reactance saturated (X'd)	14.2 %
	Short circuit transient time constant (T'd)	42 ms
	Direct axis subtransient reactance saturated (X''d)	9.8 %
	Subtransient time constant (T''d)	10.5 ms
	Quadra axis subtransient reactance saturated (X''q)	52 %
	Zero sequence reactance unsaturated (Xo)	5.4 %
	Negative sequence reactance saturated (X2)	17.1 %
	Armature time constant (Ta)	[N/A]
	No load excitation current (io)	[N/A]
	Full load excitation current (ic)	[N/A]
	Full load excitation voltage (uc)	[N/A]
	Recovery time (Delta U = 20% transitoire)	[N/A]
Motor start (Delta = 20% perm. Or 50% trans.)	[N/A]	
Transient dip (4/4 charge) – PF : 1.8 AR	[N/A]	
No load losses	[N/A]	
Heat rejection	[N/A]	



CONTROL PANEL

Standard



NEXYS

Specifications :

Frequency meter, Ammeter, Voltmeter
 Alarms and faults Oil pressure, water temperature,
 Overcrank, Overspeed (>60 kVA), Min/max alternator,
 Low fuel level, Emergency stop
 Engine parameters Hours counter, Engine speed,
 Battery voltage, Fuel level, Air preheating

Option



TELYS

Specifications :

Frequency meter, Ammeter, Voltmeter
 Alarms and faults Oil pressure, water temperature, No
 start-up, Overspeed, Min/max alternator, Min/max
 battery voltage, Low fuel level, Emergency stop
 Engine parameters Hours counter, Oil pressure, Water
 temperature, Engine speed, Battery voltage, Fuel level

