



# T16UM

Engine MITSUBISHI , S4L2-SD  
Alternator MECC ALTE , ECO 28 1L/4

## STANDARD FEATURES

- Mechanical governor
- Mechanically welded chassis with antivibration suspension
- Power circuit breaker
- Radiator for wiring T° of 50°C [122°F] max with mechanical fan
- Protective grille for fan and rotating parts
- 9dB(A) silencer supplied separately
- Charged DC starting battery with electrolyte
- 12 V charging alternator and starter
- Supplied with oil and coolant -30°C
- User manual and commissioning guide



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
240MONO	15.0 / 15.0	13.6 / 13.6	62.5	Length: 1405mm [55in] Width: 715mm [28in] Height: 1053mm [41in]	452kg [996 lbs] Net 506kg [1116 lbs] Gross



## POWER DEFINITION

**PRP** : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. A 10% overload capability is available for a period of 1 hour within 12-hour period of operation, in accordance with ISO 3046-1 –

**ESP** : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

## TERM OF USE

Standard reference conditions 25 °C Air Intlet Temp, 100 m A.S.L. 60 % relative humidity. All engine performance data based on the above mentioned maximum continuous ratings.

Type	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
 M126	75	65	Length: 1750mm [69in] Width: 715mm [28in] Height: 1230mm [48in]	600kg [1323lbs] Net 654kg [1442lbs] Gross	50 L
 M126-DW	75	65	Length: 1797mm [71in] Width: 775mm [31in] Height: 1391mm [55in]	679kg [1497lbs] Net 769kg [1695lbs] Gross	93 L





## ENGINE SPECIFICATIONS

STANDARD FEATURES	Manufacturer / Model	MITSUBISHI S4L2-SD , 4-strokes, Athmo , [N/A] 4 X
	Cylinder Arrangement	L
	Displacement	1.75L [106.8C.I.]
	Bore and Stroke	78mm [3.1in.] X 92mm [3.6in.]
	Compression ratio	22 : 1
	Rated RPM	1800 Rpm
	Piston Speed	5.52m/s [18.1ft./s]
	Max. stand by Power at rated RPM	19.58kW [26BHP]
	Frequency regulation, steady state	+/- 2.5%
	BMEP	6.74bar [98psi]
	Governor : type	MECA
EXHAUST SYSTEM	Exhaust temperature	430°C [806°F]
	Exhaust gas flow	58.3L/s [124cfm]
	Max back pressure	700mm CE [28in. WG]
FUEL SYSTEM	110% (Stand By power )	[N/A]
	100% (of the Prime Power)	5.3L/h [1.4gal/hr]
	75% (of the Prime Power)	4.2L/h [1.1gal/hr]
	50% (of the Prime Power)	3.3L/h [0.9gal/hr]
	Max. fuel pump flow	18L/h [4.8gal/hr]
OIL SYSTEM	Total oil capacity w/filters	5.9L [1.6gal]
	Oil Pressure low idle	1bar [14.5psi]
	Oil Pressure rated RPM	4bar [58.0psi]
	Oil consumption 100% load	0.03L/h [0.008gal/hr]
	Oil capacity carter	5.4L [1.4gal]
THERMAL BALANCE	Heat rejection to exhaust	16kW [910Btu/mn]
	Radiated heat to ambient	2.5kW [142Btu/mn]
	Heat rejection to coolant	17kW [967Btu/mn]
AIR INTAKE	Max. intake restriction	200mm CE [8in. WG]
	Engine air flow	21.7L/s [46cfm]
COOLANT SYSTEM	Radiator & engine capacity	4.9L [1.3gal]
	Max water temperature	111°C [232°F]
	Outlet water temperature	93°C [199°F]
	Fan power	0.9 kW
	Fan air flow w/o restriction	0.9m3/s [1907cfm]
	Available restriction on air flow	10mm CE [0.4in. WG]
	Type of coolant	Gencool
	Thermostat	82-95 °C
EMISSIONS LEVEL	PM	N/A
	CO	N/A
	Nox	N/A
	HC	N/A





## ALTERNATOR SPECIFICATIONS

GENERAL  DATAS	Manufacturer	MECC ALTE
	Type	ECO 28 1L/4
	Number of phase	1
	Power factor (Cos Phi)	1
	Altitude	1000
	Overspeed	[N/A]
	Pole : number	4
	Exciter type	NO
	Insulation : class, temperature rise	H / H
	Voltage regulator	AVR
	Total harmonics (TGH/THC)	[N/A]
	Wave form : NEMA = TIF – TGH/THC	[N/A]
	Wave form : CEI = FHT – TGH/THC	2
	Bearing : number	1
	Coupling	Direct
	Voltage regulation 0 to 100% load	[N/A]
Recovery time (20% Volt dip) ms	[N/A]	
SKVA with 90% of nominal sustained voltage (at 0.4PF)	N/A	
OTHER  DATAS	Continuous nominal rating @ 40°C	[N/A]
	Standby rating @ 27°C	16 kVA
	Efficiencies @ 4/4 load	84.2 %
	Air flow	0.096m <sup>3</sup> /s [203.41cfm]
	Short circuit ratio;50 (Kcc)	0.65
	Direct axis synchro reactance unsaturated (Xd)	175 %
	Quadra axis synchro reactance unsaturated (Xq)	76 %
	Open circuit time constant;50 (T'do)	0.87 ms
	Direct axis transient reactance saturated (X'd)	16.5 %
	Short circuit transient time constant (T'd)	0.045 ms
	Direct axis subtransient reactance saturated (X''d)	9.4 %
	Subtransient time constant (T''d)	0.015 ms
	Quadra axis subtransient reactance saturated (X''q)	21 %
	Zero sequence reactance unsaturated (Xo)	3.2 %
	Negative sequence reactance saturated (X2)	14.2 %
	Armature time constant (Ta)	0.013 ms
	No load excitation current (io)	[N/A]
	Full load excitation current (ic)	[N/A]
	Full load excitation voltage (uc)	[N/A]
	Recovery time (Delta U = 20% transitoire)	[N/A]
	Motor start (Delta = 20% perm. Or 50% trans.)	[N/A]
	Transient dip (4/4 charge) – PF : 1.8 AR	[N/A]
	No load losses	[N/A]
	Heat rejection	[N/A]



## CONTROL PANEL

### Standard



### NEXYS

#### Specifications :

Frequency meter, Ammeter, Voltmeter  
Alarms and faults Oil pressure, water temperature,  
Overcrank, Overspeed (>60 kVA), Min/max alternator,  
Low fuel level, Emergency stop  
Engine parameters Hours counter, Engine speed,  
Battery voltage, Fuel level, Air preheating

### Option



### TELYS

#### Specifications :

Frequency meter, Ammeter, Voltmeter  
Alarms and faults Oil pressure, water temperature, No  
start-up, Overspeed, Min/max alternator, Min/max  
battery voltage, Low fuel level, Emergency stop  
Engine parameters Hours counter, Oil pressure, Water  
temperature, Engine speed, Battery voltage, Fuel level

