

V400U

Engine VOLVO , TAD1242GE
Alternator LEROY SOMER , LSA472VS3

STANDARD FEATURES

- Electronic governor
- Mechanically welded chassis with antivibration suspension
- Power circuit breaker
- Radiator for wiring T° of 50°C [122°F] max with mechanical fan
- Protective grille for fan and rotating parts
- 9dB(A) silencer supplied separately
- Charged DC starting battery with electrolyte
- 24 V charging alternator and starter
- Supplied with oil and coolant -30°C
- User manual and commissioning guide



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
480/277	400 / 500	364 / 455	601	Length: 3160mm [124in] Width: 1340mm [53in] Height: 1805mm [71in]	3238kg [7139 lbs] Net 3718kg [8197 lbs] Gross
440/254	400 / 500	364 / 455	656		
380/220	400 / 500	364 / 455	760		
240/120	387 / 484	352 / 440	1164		
230/115	380 / 475	345 / 432	1192		
220/127	400 / 500	364 / 455	1312		
208/120	400 / 500	364 / 455	1388		
600/347	400 / 500	364 / 455	481		



POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. A 10% overload capability is available for a period of 1 hour within 12-hour period of operation, in accordance with ISO 3046-1 –

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions 40 °C Air Inlet Temp, 1100 m A.S.L. 60 % relative humidity. All engine performance data based on the above mentioned maximum continuous ratings.

Type	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
 M228	83	73	Length: 4475mm [176in] Width: 1410mm [56in] Height: 2430mm [96in]	4320kg [9524lbs] Net 4790kg [10560lbs] Gross	470 L
 M228-DW	83	73	Length: 4527mm [178in] Width: 1410mm [56in] Height: 2700mm [106in]	4670kg [10296lbs] Net 5984kg [13192lbs] Gross	1368 L





ENGINE SPECIFICATIONS

STANDARD FEATURES	Manufacturer / Model	VOLVO TAD1242GE , 4-strokes, Turbo , Air/Air DC 6 X
	Cylinder Arrangement	L
	Displacement	12.13L [740.2C.I.]
	Bore and Stroke	131mm [5.2in.] X 150mm [5.9in.]
	Compression ratio	17.5 : 1
	Rated RPM	1800 Rpm
	Piston Speed	9m/s [29.5ft./s]
	Max. stand by Power at rated RPM	430kW [576BHP]
	Frequency regulation, steady state	+/- 0.5%
	BMEP	22.5bar [326psi]
Governor : type	ELEC	
EXHAUST SYSTEM	Exhaust temperature	505°C [941°F]
	Exhaust gas flow	1250L/s [2649cfm]
	Max back pressure	1000mm CE [39in. WG]
FUEL SYSTEM	110% (Stand By power)	106L/h [28.0gal/hr]
	100% (of the Prime Power)	92.7L/h [24.5gal/hr]
	75% (of the Prime Power)	67.8L/h [17.9gal/hr]
	50% (of the Prime Power)	45.5L/h [12.0gal/hr]
	Max. fuel pump flow	150L/h [39.6gal/hr]
OIL SYSTEM	Total oil capacity w/filters	35L [9.2gal]
	Oil Pressure low idle	2.5bar [36.2psi]
	Oil Pressure rated RPM	5.5bar [79.7psi]
	Oil consumption 100% load	0.14L/h [0.037gal/hr]
	Oil capacity carter	31L [8.2gal]
THERMAL BALANCE	Heat rejection to exhaust	272kW [15466Btu/mn]
	Radiated heat to ambient	20kW [1137Btu/mn]
	Heat rejection to coolant	139kW [7904Btu/mn]
AIR INTAKE	Max. intake restriction	500mm CE [20in. WG]
	Engine air flow	500L/s [1060cfm]
COOLANT SYSTEM	Radiator & engine capacity	44L [11.6gal]
	Max water temperature	103°C [217°F]
	Outlet water temperature	93°C [199°F]
	Fan power	19 kW
	Fan air flow w/o restriction	10.3m ³ /s [21827cfm]
	Available restriction on air flow	47mm CE [1.9in. WG]
	Type of coolant	Glycol-Ethylene
	Thermostat	82-95 °C
EMISSIONS LEVEL	PM	0.07 gr/bhp/h
	CO	0.37 gr/bhp/h
	HC/Nox	4.33 gr/bhp/h

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries – 12bis rue de la Villeneuve – CS 92848 – 29 228 BREST CEDEX 2

Tel +33 (0)2 98 41 41 41 – Fax : +33 (0)2 98 41 63 07 – www.sdmo.com





ALTERNATOR SPECIFICATIONS

GENERAL DATAS	Manufacturer	LEROY SOMER
	Type	LSA472VS3
	Number of phase	3
	Power factor (Cos Phi)	0.8
	Altitude	< 1000 m
	Overspeed	2250 rpm
	Pole : number	4
	Exciter type	SHUNT
	Insulation : class, temperature rise	H / H
	Voltage regulator	R230
	Total harmonics (TGH/THC)	< 4%
	Wave form : NEMA = TIF – TGH/THC	< 50
	Wave form : CEI = FHT – TGH/THC	< 2%
	Bearing : number	1
	Coupling	Direct
	Voltage regulation 0 to 100% load	+/- 0.5%
	Recovery time (20% Volt dip) ms	500 ms
	SkVA with 90% of nominal sustained voltage (at 0.4PF)	N/A
OTHER DATAS	Continuous nominal rating @ 40°C	466 kVA
	Standby rating @ 27°C	545 kVA
	Efficiencies @ 4/4 load	93.3 %
	Air flow	1.1m3/s [2330.76cfm]
	Short circuit ratio;50 (Kcc)	0.29
	Direct axis synchro reactance unsaturated (Xd)	405 %
	Quadra axis synchro reactance unsaturated (Xq)	243 %
	Open circuit time constant;50 (T'do)	1771 ms
	Direct axis transient reactance saturated (X'd)	22.8 %
	Short circuit transient time constant (T'd)	100 ms
	Direct axis subtransient reactance saturated (X''d)	18.3 %
	Subtransient time constant (T''d)	10 ms
	Quadra axis subtransient reactance saturated (X''q)	24.7 %
	Zero sequence reactance unsaturated (Xo)	1 %
	Negative sequence reactance saturated (X2)	21.5 %
	Armature time constant (Ta)	15 ms
	No load excitation current (io)	0.9 A
	Full load excitation current (ic)	4 A
	Full load excitation voltage (uc)	40 V
	Recovery time (Delta U = 20% transitoire)	500 ms
	Motor start (Delta = 20% perm. Or 50% trans.)	973 kVA
	Transient dip (4/4 charge) – PF : 1.8 AR	18.5 %
	No load losses	8.15 kW
Heat rejection	28.18 kW	



CONTROL PANEL

Standard



TELYS

Specifications :

- Frequency meter, Ammeter, Voltmeter
- Alarms and faults Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop
- Engine parameters Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level

Option



KERYS

Specifications :

- Frequency meter, Ammeter, Voltmeter
- Alarms and faults Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop
- Engine parameters Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level
- Additional specifications Website, Troubleshooting, Assistance and Maintenance, Plotting and logging, Load impact, 8 configurations available, Compliance with international standards...

