

M127

Soundproofing canopy

Standard Specifications

- They protect stationary and mobile generator against the bad weather, against the theft and enables the reduction of the noise level.
- Enclosures are of 12 gauge steel. Steel sheet are electro zinc coated before painting (inside and outside) with a polyester powder rust inhibiting coat .
- High corrosion resistance: stainless covered with zinc and made in dichromate, bolts and rivets, anodized aluminium alloy hinges flexible seals between body sections.
- Soundfoam between 20 and 50 mm (1 to 2 in) acoustical sound treatment
- Lifting eye(s) on top of the enclosure fixed to the skid
- Large doors allow easy access to the generator set for service and monitoring purposes
- Window in "securit" glass mounted on enclosure door for control viewing .
- A critical silencer is mounted inside the enclosure
- Emergency stop button is accessible from outside enclosure.



| GENSET | Sound level | | | Dimensions (mm) | Weight (kgs) | Tank (l) |
|---------|-------------|----------|-----------|--------------------|-----------------|-------------|
| | dB(A)@1m | dB(A)@7m | dB(A)@15m | | | |
| T40UC4i | 73.4 | 63.4 | 59.4 | 2080 x 960 x 1415 | 920 | 100 |

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

